



FUKUCOM COMPANY LTD.

福 靈 有 限 公 司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206


1N4150

Silicon Epitaxial Planar Switching Diode

for general purpose switching applications

Features

- Fast switching speed
- High reliability



Glass Case DO-35
Dimensions in mm


Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	50	V
Forward Continuous Current	I_{FM}	300	mA
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Power Dissipation	P_{tot}	500 ¹⁾	mW
Junction Temperature	T_j	200	$^\circ\text{C}$
Operating and Storage Temperature Range	T_{stg}	- 65 to + 175	$^\circ\text{C}$

¹⁾ Valid provided that leads are at a distance of 8 mm from case kept at ambient temperature

Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Max.	Unit
Forward Voltage at $I_F = 200\text{ mA}$	V_F	1.2	V
Reverse Current at $V_R = 50\text{ V}$	I_R	100	nA
Reverse Recovery Time at $I_F = I_R = 200\text{ mA}$, $I_{rr} = 0.1 \times I_R$, $R_L = 100\ \Omega$	t_{rr}	4	ns



Dated : 15/06/2009