



FUKUCOM COMPANY LTD.

福靈有限公司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206

BAS316WS


High Speed Diode

Applications

- High-speed switching

PINNING

PIN	DESCRIPTION
1	Cathode
2	Anode




Absolute Maximum Ratings ($T_a = 25\text{ }^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage	V_{RRM}	100	V
Reverse Voltage	V_R	100	V
Continuous Forward Current	I_F	250	mA
Repetitive Peak Forward Current	I_{FRM}	500	mA
Non-Repetitive Peak Forward Current	I_{FSM}	4 1 0.5	A
		$t = 1\ \mu\text{s}$ $t = 1\ \text{ms}$ $t = 1\ \text{s}$	
Total Power Dissipation	P_{tot}	400	mW
Thermal Resistance from Junction to Soldering Point	$R_{th(j-s)}$	150	K/W
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature Range	T_s	- 65 to + 150	$^\circ\text{C}$

Characteristics at $T_a = 25\text{ }^\circ\text{C}$

Parameter	Symbol	Max.	Unit
Forward Voltage at $I_F = 1\ \text{mA}$ at $I_F = 10\ \text{mA}$ at $I_F = 50\ \text{mA}$ at $I_F = 150\ \text{mA}$	V_F	0.715 0.855 1 1.25	V
Reverse Current at $V_R = 25\ \text{V}$ at $V_R = 75\ \text{V}$ at $V_R = 25\ \text{V}$, $T_J = 150\text{ }^\circ\text{C}$ at $V_R = 75\ \text{V}$, $T_J = 150\text{ }^\circ\text{C}$	I_R	30 1 30 50	nA μA μA μA
Diode Capacitance at $V_R = 0\ \text{V}$, $f = 1\ \text{MHz}$	C_{tot}	1.5	pF
Forward Recovery Voltage at $I_F = 10\ \text{mA}$, $t_r = 20\ \text{ns}$	V_{fr}	1.75	V
Reverse Recovery Time at $I_F = 10\ \text{mA}$ to $I_R = 10\ \text{mA}$, Measured at $I_R = 1\ \text{mA}$, $R_L = 100\ \Omega$	t_{rr}	4	ns



Dated : 29/11/2006



FUKUCOM COMPANY LTD.

福靈有限公司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,
KWUN TONG, KOWLOON, HONG KONG.

TEL: 852-2790 0314 FAX: 852-2790 0206

BAS316WS






Fig. 1 Maximum permissible continuous forward current as a function of soldering point temperature.



(1) $T_j = 150^\circ\text{C}$; typical values.
(2) $T_j = 25^\circ\text{C}$; typical values.
(3) $T_j = 25^\circ\text{C}$; maximum values.

Fig. 2 Forward current as a function of forward voltage.



Based on square wave currents.
 $T_j = 25^\circ\text{C}$ prior to surge.

Fig. 3 Maximum permissible non-repetitive peak forward current as a function of pulse duration.






Fig. 4 Reverse current as a function of junction temperature.



$f = 1\text{ MHz}$; $T_j = 25^\circ\text{C}$.

Fig. 5 Diode capacitance as a function of reverse voltage; typical values.





FUKUCOM COMPANY LTD.

福靈有限公司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,
KWUN TONG, KOWLOON, HONG KONG.


TEL: 852-2790 0314 FAX: 852-2790 0206

BAS316WS


PACKAGE OUTLINE

Plastic surface mounted package; 2 leads

SOD-323



UNIT	A	b_p	C	D	E	H_E
mm	1.10 0.80	0.40 0.25	0.15 0.00	1.80 1.60	1.35 1.15	2.80 2.30



Dated : 29/11/2006