



FUKUCOM COMPANY LTD.

福 靈 有 限 公 司

FLAT P, 3/F., EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.


TEL: 852-2790 0314 FAX: 852-2790 0206

## BAV101~BAV103

### Silicon Epitaxial Planar Diodes

High Voltage Switching Diodes

LL-34




Glass case MiniMELF  
Dimensions in mm

#### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Repetitive Peak Reverse Voltage BAV101 BAV102 BAV103	$V_{RRM}$	120	V
		200	
		250	
Reverse Voltage BAV101 BAV102 BAV103	$V_R$	100	V
		150	
		200	
Continuous Forward Current	$I_F$	250	mA
Repetitive Peak Forward Current	$I_{FRM}$	625	mA
Non-repetitive Peak Forward Surge Current at $t = 1\text{ s}$ at $t = 100\text{ }\mu\text{s}$ at $t = 1\text{ }\mu\text{s}$	$I_{FSM}$	1	A
		3	
		9	
Total Power Dissipation	$P_{tot}$	400	mW
Junction Temperature	$T_j$	175	$^\circ\text{C}$
Storage Temperature Range	$T_{stg}$	- 65 to + 175	$^\circ\text{C}$

#### Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Max.	Unit
Forward Voltage at $I_F = 100\text{ mA}$ at $I_F = 200\text{ mA}$	$V_F$	1 1.25	V
Reverse Current at $V_R = 100\text{ V}$ at $V_R = 150\text{ V}$ at $V_R = 200\text{ V}$ at $V_R = 100\text{ V}, T_j = 150\text{ }^\circ\text{C}$ at $V_R = 150\text{ V}, T_j = 150\text{ }^\circ\text{C}$ at $V_R = 200\text{ V}, T_j = 150\text{ }^\circ\text{C}$	$I_R$	100	nA
		100	nA
		100	nA
		100	$\mu\text{A}$
Diode Capacitance at $V_R = 0, f = 1\text{ MHz}$	$C_d$	5	pF
Reverse Recovery Time at $I_F = I_R = 30\text{ mA}, I_{rr} = 3\text{ mA}, R_L = 100\text{ }\Omega$	$t_{rr}$	50	ns



Dated : 15/06/2009




# FUKUCOM COMPANY LTD.

## 福 靈 有 限 公 司

FLAT P, 3/F, EVEREST INDUSTRIAL CENTRE, 396 KWUN TONG ROAD,  
KWUN TONG, KOWLOON, HONG KONG.


TEL: 852-2790 0314 FAX: 852-2790 0206

### BAV101~BAV103




Device mounted on an FR4 printed-circuit board.

Maximum permissible continuous forward current as a function of ambient temperature.




- (1)  $T_J = 150$  °C; typical values.
- (2)  $T_J = 25$  °C; typical values.
- (3)  $T_J = 25$  °C; maximum values.

Forward current as a function of forward voltage.




Based on square wave currents.  
 $T_J = 25$  °C prior to surge.

Maximum permissible non-repetitive peak forward current as a function of pulse duration.




$V_R = V_{Rmax}$ .  
Solid line; maximum values.  
Dotted line; typical values.

Reverse current as a function of junction temperature.



$f = 1$  MHz;  $T_J = 25$  °C.

Diode capacitance as a function of reverse voltage; typical values.



Dated : 15/06/2009